

ANDAM

ANDAM GAL-C

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	**ew**
Working width (m)	**GAL-C 2,5: 2,5 · GAL-C 3,0: 3,0 · GAL-C 3,5: 3,5 · GAL-C 4,0: 4,0 · GAL-C 4,0 H: 4,0 · GAL-C 4,5 H: 4,5 · GAL-C 5,0 H: 5,0 · GAL-C 6,0 H: 6,0**
Number of discs	**GAL-C 2,5: 20 · GAL-C 3,0: 24 · GAL-C 3,5: 28 · GAL-C 4,0: 32 · GAL-C 4,0 H: 32 · GAL-C 4,5 H: 36 · GAL-C 5,0 H: 42 · GAL-C 6,0 H: 48**
Disc diameter (mm)	**GAL-C 2,5: 560 · GAL-C 3,0: 560 · GAL-C 3,5: 560 · GAL-C 4,0: 560 · GAL-C 4,0 H: 560 · GAL-C 4,5 H: 560 · GAL-C 5,0 H: 560 · GAL-C 6,0 H: 560**
Weight (kg)	**GAL-C 2,5: 1208 · GAL-C 3,0: 1314 · GAL-C 3,5: 1495 · GAL-C 4,0: 1849 · GAL-C 4,0 H: 2215 · GAL-C 4,5 H: 2395 · GAL-C 5,0 H: 2586 · GAL-C 6,0 H: 2923**
Required power (hp)	**GAL-C 2,5: 80 · GAL-C 3,0: 100 · GAL-C 3,5: 120 · GAL-C 4,0: 140 · GAL-C 4,0 H: 160 · GAL-C 4,5 H: 170 · GAL-C 5,0 H: 180 · GAL-C 6,0 H: 200**

БЕЛЕЖКИ

The GAL-C short disc harrows are fitted with two rows of serrated pine steel discs, 560 mm in diameter, mounted on hubs with fully sealed, maintenance-free bearings. The working units are attached to the frame via rubber suspension rollers. A wide range of optional accessories is available, including a variety of rollers, scrapers, protective grilles and more.

СНИМКИ

Докоснете снимка, за да я отворите в пълен размер.



