

MANDAM

MANDAM GAL-K

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	**New**	Working width (m)	**GAL-K 4,0 H: 4,0 · GAL-K 5,0 H: 5,0 · GAL-K 6,0 H: 6,0 · GAL-K 8,0 H: 8,0 · GAL-K 10,0 H: 10,0 · GAL-K 12,0 H : 12,0**
Number of discs	**GAL-K 4,0 H: 32 · GAL-K 5,0 H: 40 · GAL-K 6,0 H: 48 · GAL-K 8,0 H: 64 · GAL-K 10,0 H: 80 · GAL-K 12,0 H: 96**	Disc diameter (mm)	**GAL-K 4,0 H: 560 · GAL-K 5,0 H: 560 · GAL-K 6,0 H: 560 · GAL-K 8,0 H: 560 · GAL-K 10,0 H: 560 · GAL-K 12,0 H : 560**
Weight (kg)	**GAL-K 4,0 H: 3508 · GAL-K 5,0 H: 3963 · GAL-K 6,0 H: 4461 · GAL-K 8,0 H: 5576 · GAL-K 10,0 H: 8500 · GAL-K 12,0 H: 9200**	Required power (hp)	**GAL-K 4,0 H: 150 · GAL-K 5,0 H: 180 · GAL-K 6,0 H: 200 · GAL-K 8,0 H: 220 · GAL-K 10,0 H: 380 · GAL-K 12,0 H : 420**

БЕЛЕЖКИ

he 8-metre-wide GAL-K disc harrow is designed for pre-sowing and post-harvest soil cultivation. It is built on a sturdy frame with serrated discs made of pine steel, each with a diameter of 560 mm. The working units are attached to the frame via rubber suspension rollers, whilst the reinforced, maintenance-free bearings ensure durability. The pre-set angle of attack of the discs is optimised for effective penetration, whilst high-quality materials ensure exceptional durability. Hydraulic working depth adjustment and a transport chassis with pneumatic brakes are included as standard.

СНИМКИ

Докоснете снимка, за да я отворите в пълен размер.







