

MANDAM

MANDAM MCB

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	**New**
Working bodies	**MCB 2,5 525: 43 · MCB 3,0 525: 51 · MCB 4,5 H 525: 85 · MCB 6,2 H 525: 123 · MCB 8,0 H 525: 151 · MCB 12,3 H 525: 247**
Weight (kg)	**MCB 2,5 525: 980 · MCB 3,0 525: 1160 · MCB 4,5 H 525: 2272 · MCB 6,2 H 525: 2970 · MCB 8,0 H 525: 3825 · MCB 12,3 H 525: 7140**
Working width (m)	**MCB 2,5 525: 2.5 · MCB 3,0 525: 3.0 · MCB 4,5 H 525: 4.5 · MCB 6,2 H 525: 6.2 · MCB 8,0 H 525: 8.0 · MCB 12,3 H 525: 12.3**
Working parts – diameter (mm)	**MCB 2,5 525: 525 · MCB 3,0 525: 525 · MCB 4,5 H 525: 525 · MCB 6,2 H 525: 525 · MCB 8,0 H 525: 525 · MCB 12,3 H 525: 525**
Required power (hp)	**MCB 2,5 525: 45 · MCB 3,0 525: 60 · MCB 4,5 H 525: 80 · MCB 6,2 H 525: 120 · MCB 8,0 H 525: 160 · MCB 12,3 H 525: 180**

БЕЛЕЖКИ

MANDAM MCB Cambridge rollers can be used after harvest to speed up the decomposition of straw and crop residues. They are also suitable for working on grassed areas and meadows. Their main function is to level the field, retain moisture in the soil and improve its structure. The working elements consist of cast-iron wheels with a diameter of 525 mm.

СНИМКИ

Докоснете снимка, за да я отворите в пълен размер.





