

SIPTEC

SIPTEC DRACON

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	**New**
Transport width (m)	**Dracon² 250: 2,5 · Dracon² 300: 3,0 · Dracon² 350: 3,5 · Dracon² 400: 4,0 · Dracon² R 400: 3,0 · Dracon² R 500: 3,0**
Number of discs	**Dracon² 250: 6 · Dracon² 300: 8 · Dracon² 350: 8 · Dracon² 400: 10 · Dracon² R 400: 10 · Dracon² R 500: 12**
Required power (hp)	**Dracon² 250: 70-130 · Dracon² 300: 90-170 · Dracon² 350: 100-180 · Dracon² 400: 120-200 · Dracon² R 400: 120-200 · Dracon² R 500: 150-240**
Working width (m)	**Dracon² 250: 2,5 · Dracon² 300: 3,0 · Dracon² 350: 3,5 · Dracon² 400: 4,0 · Dracon² R 400: 4,0 · Dracon² R 500: 5,0**
Number of teeth	**Dracon² 250: 6 · Dracon² 300: 7 · Dracon² 350: 8 · Dracon² 400: 9 · Dracon² R 400: 9 · Dracon² R 500: 11**
Weight (kg)	**Dracon² 250: 710 · Dracon² 300: 810 · Dracon² 350: 945 · Dracon² 400: 1080 · Dracon² R 400: 1410 · Dracon² R 500: 1780**

БЕЛЕЖКИ

The SIPTEC Dracon² is a high-performance stubble cultivator with a long service life. The robust central frame operates at depths of up to 35 cm, even under demanding conditions, thanks to its hydro-pneumatic overload protection. The standard equipment includes the lower blade, the guide plate and the side wings.

The standard levelling discs, mounted in pairs on a rubber suspension system, level both mixed and tilled soil. Behind the rear roller, the tillage is consistent, precise and well-balanced.

It combines effective soil cultivation after harvest with reduced fuel consumption. The soil is levelled and loosened, whilst stubble is converted into organic fertiliser without the need for further tillage.

2 rows of working bodies
Robust frame 100x100x8 mm
Row spacing 750 mm
Working depth up to 350 mm
Wings 275 mm
Levelling discs with rubber blocks

СНИМКИ

Докоснете снимка, за да я отворите в пълен размер.

