

SIPTEC

SIPTEC DSB

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	**New**
Number of discs	**DSB 28: 28 · DSB 36: 32 · DST 36: 36 · DSB 40: 40**
Required power (hp)	**DSB 28: 90-100 · DSB 36: 100-120 · DST 36: 120-140 · DSB 40: 140-160**
Working width (m)	**DSB 28: 3.0 · DSB 36: 3.4 · DST 36: 3.8 · DSB 40: 4.2**
Weight (kg)	**DSB 28: 1510 · DSB 36: 1580 · DST 36: 1870 · DSB 40: 1950**

БЕЛЕЖКИ

SIPTEC DSB mounted disc harrows are designed for tractors with a power output of 90 to 160 k.s. and are fitted with 2 8 to 40 discs, each with a diameter of 560 mm. The disc sections operate in an X-shape, whilst the main frame is c onstructed from an exceptionally robust central beam profile measuring 220 x 120 mm. The DSB series provides exc ellent visibility whilst working and easy access to all maintenance points. The angle of attack of the front disc secti ons is adjustable independently of that of the rear sections. The disc angle is adjusted manually, with an option for hydraulic control of the disc section angle also available. The DSB series is fitted as standard with a hydraulic liftin g system for easy manoeuvring and road transport.

railed design with X-shaped disc sections
ain frame made from a single 220 x 120 mm beam
28, 32, 36 or 40 reinforced discs, Ø560 mm
Distance between discs: 200 mm
anually adjustable angle of attack of the disc sections
draulic lifting system for manoeuvring and transport
igh-load-bearing bearings
Disc axle: 30 x 30 mm
Individually adjustable disc scrapers

СНИМКИ

Докоснете снимка, за да я отворите в пълен размер.

