

SIPTEC

SIPTEC MINI MAX

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	**New**	Working width (m)	**MiniMax 150: 1,3 · MiniMax 190: 1,7 · MiniMax 230: 2,1 · MiniMax 250: 2,3**
Transport width (m)	**MiniMax 150: 1,5 · MiniMax 190: 1,9 · MiniMax 230: 2,3 · MiniMax 250: 2,5**	Number of discs	**MiniMax 150: 10 · MiniMax 190: 12 · MiniMax 230: 16 · MiniMax 250: 18**
Weight (kg)	**MiniMax 150: 562 · MiniMax 190: 620 · MiniMax 230: 675 · MiniMax 250: 732**	Required power (hp)	**MiniMax 150: 60-80 · MiniMax 190: 70-80 · MiniMax 230: 80-100 · MiniMax 250: 90-110**

БЕЛЕЖКИ

Агротехники & Ко
Get in touch
070090033 · info@agrotehniki.com · www.agrotehniki.com

SIPTEC MINI MAX

The MiniMax series, ranging from 1.5 m to 2.5 m, delivers excellent results on heavy and compacted soils. The individual mounts for each disc process crop residues and weeds with high capacity. The robust frame, minimal wear and maintenance-free bearings are among its key features. The high working speed, thanks to the MiniMax models' excellent soil penetration, ensures economical operation. It is designed for vineyards and vegetable crops, for weed control and to replace the time-consuming process of using a rotary tiller.

Rigid frame
8 to 16 reinforced serrated discs, Ø520 mm
Protective system with rubber blocks Ø40 mm
Manually adjustable rear roller
High-load-bearing, maintenance-free bearings
Suitable for vineyards and orchards