

SIPTEC

SIPTEC MTX

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	**ew**
Number of discs	**X 20: 20 · MTX 24: 24 · MTX 28: 28 · MTX 32: 32**
Required power (hp)	**X 20: 40-65 · MTX 24: 45-75 · MTX 28: 55-85 · MTX 32: 60-90**
Working width (m)	**X 20: 2,1 · MTX 24: 2,5 · MTX 28: 2,9 · MTX 32: 3,4**
Weight (kg)	**X 20: 605 · MTX 24: 680 · MTX 28: 752 · MTX 32: 835**

БЕЛЕЖКИ

Агротехники & Ко
Get in touch
070090033 · info@agrotehniki.com · www.agrotehniki.com

he MTX disc harrow for mounted installation features working sections arranged in an X-shape. It is the lightest in it s class, offering high manoeuvrability and compact dimensions. The MTX's main frame is made from a 70 x 70 mm sq uare section, and the working angle is adjusted manually. All MTX models are fitted with 8 high-capacity bearings supp orting a 30 x 30 mm shaft. The wear-resistant Ø510 mm discs are cleaned by individually adjustable scrapers.

Category 2 three-point hitch
70 x 70 mm frame
Easy manual adjustment of the working angle via pins
Distance between discs: 200 mm
Independent scrapers for all discs
Ø510 mm discs with a smooth, toothed arrangement
8 bearing hubs with a total of 16 ball bearings
Central reinforced S-tooth for precise levelling