

SIPTEC

SIPTEC RY

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	**New**	Working width (m)	**RY 5: 2.5 · RY 7: 3.0 · RY 7: 3.5 · RY 9: 4.0 · RY 11: 5.0**
Transport width (m)	**RY 5: 2.5 · RY 7: 3.0 · RY 7: 3.5 · RY 9: 4.0 · RY 11: 5.0**	Number of teeth	**RY 5: 5 · RY 7: 7 · RY 7: 7 · RY 9: 9 · RY 11: 11**
Weight (kg)	**RY 5: 1120 · RY 7: 1490 · RY 7: 1640 · RY 9: 1860 · RY 11: 2230**	Required power (hp)	**RY 5: 140-160 · RY 7: 180-250 · RY 7: 180-250 · RY 9: 250-350 · RY 11: 350-500**

БЕЛЕЖКИ

Агротехники & Ко
Get in touch

070090033 · info@agrotehniki.com · www.agrotehniki.com

The SIPTEC RY series enables fast, high-quality work to a depth of 65 cm and a width of 2.5 to 5 m. They are suitable for tractors with a power output of 130–500 k.s. The soil is lifted and, as it falls back, it cracks, which loosens all the soil layers. At the same time, clods are broken up and the surface is recompacted.

The aggressive positioning and shape of the working bodies ensure easy penetration. The working bodies are arranged in two rows, and overload protection is provided by shear bolts located at the top of each working body for easy replacement. The working elements are made from special, durable steel with a long service life.

Two support legs ensure easy and safe parking.

3-point hitch system
Sturdy frame 120x120x10 mm
Working depth up to 65 cm
Ground clearance under the frame 920 mm
Overload protection with shear bolts
Working tools made from durable steel
Support legs for safe storage
Rotating blades on both sides of each working tool

СНИМКИ

Докоснете снимка, за да я отворите в пълен размер.





