

SIPTEC

SIPTEC VIBRO PRO

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	ew
ransport width (m)	VibroPro 400: 2,4 · VibroPro 450: 2,4 · VibroPro 500: 2,4 · VibroPro 600: 2,4 · VibroPro 700: 2,4 · VibroPro 800 : 2,4 · VibroPro 900: 2,4
Weight (kg)	VibroPro 400: 1050 · VibroPro 450: 1100 · VibroPro 500: 1230 · VibroPro 600: 1370 · VibroPro 700: 1540 · VibroPro 800: 1950 · VibroPro 900: 2450
Working width (m)	VibroPro 400: 4,0 · VibroPro 450: 4,5 · VibroPro 500: 5,0 · VibroPro 600: 6,0 · VibroPro 700: 7,0 · VibroPro 800 : 8,0 · VibroPro 900: 9,0
Number of S-shaped teeth	VibroPro 400: 36 · VibroPro 450: 38 · VibroPro 500: 42 · VibroPro 600: 48 · VibroPro 700: 58 · VibroPro 800 : 68 · VibroPro 900: 76
Required power (hp)	VibroPro 400: 100-110 · VibroPro 450: 110-120 · VibroPro 500: 120-130 · VibroPro 600: 130-160 · VibroPro 700: 160-180 · VibroPro 800: 200-250 · VibroPro 900 : 250-300

БЕЛЕЖКИ

Агротехники & Ко
Get in touch
070090033 · info@agrotehniki.com · www.agrotehniki.com

SIPTEC VibroPro hydraulically folding frame combination for seedbed preparation with a working width of up to 9 m.

he robust construction, the S-shaped working elements arranged in four rows, and the adjustable twin rear crumbling r oller level the soil, improve aeration, penetration and the incorporation of crop residues. This is agricultural machinery fo r mixing and crumbling the soil prior to sowing. It removes remaining weeds, aerates and loosens the soil, and cre ates a suitable seedbed. Modern design for high demands on performance and soil cultivation.

3-point hitch system, Cat. 2, Cat. 3 for VibroPro 800–900
Robust, hydraulically folding frame
4 rows of S-shaped working bodies made from 50x50 mm square sections
Reinforced, adjustable, twin rear crumbling rollers, Ø310 mm, with bearings; shaft Ø30 mm

СНИМКИ

Докоснете снимка, за да я отворите в пълен размер.



