

SIPTEC

SIPTEC VRIBRO PRO M

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	ew
ransport width (m)	VibroPro M 400: 2,4 · VibroP o M 450: 2,4 · VibroPro M 500: 2,4 · V ibroPro M 600: 2,4
Weight (kg)	VibroPro M 400: 945 · VibroP o M 450: 990 · VibroPro M 500: 1105 · VibroPro M 600: 1235
Working width (m)	VibroPro M 400: 4,0 · VibroP o M 450: 4,5 · VibroPro M 500: 5,0 · V ibroPro M 600: 6,0
Number of S-shaped teeth	VibroPro M 400: 36 · VibroP o M 450: 38 · VibroPro M 500: 42 · Vi broPro M 600: 50
Required power (hp)	VibroPro M 400: 80-110 · VibroP o M 450: 90-120 · VibroPro M 5 00: 100-130 · VibroPro M 600: 110-160

БЕЛЕЖКИ

SIPTEC VRIBRO PRO M hydraulically folding frame combination for seedbed preparation with a working width of p to 6 m.

he robust construction, the S-shaped working elements arranged in four rows, and the adjustable twin rear crumbling ro ller level the soil, improve aeration, penetration and the incorporation of crop residues. Agricultural implement for mixi ng and crumbling the soil prior to sowing. Removes remaining weeds, aerates and loosens the soil, creating an ideal seedbed. Modern design for high demands on productivity and soil cultivation.

ategory 2 three-point hitch
Robust, hydraulically folding frame
4 rows of S-shaped working bodies made from 50x50 mm square sections
Reinforced, adjustable, double rear crumbling roller Ø310 mm with bearings, shaft Ø30 mm

СНИМКИ

Докоснете снимка, за да я отворите в пълен размер.





