

YUKAY

YUKAY BARLAS

● Налично

ТЕХНИЧЕСКИ ДАННИ

Състояние	**New**
Working width (mm)	**2.00 m.: 2440 · 2.25 m.: 2690 · 2.50 m.: 2940 · 2.75 m.: 3190 · 3.00 m.: 3440 · 3.50 m.: 4160 · 4.00 m.: 4660**
Seed hopper (L)	**2.00 m.: 620 · 2.25 m.: 700 · 2.50 m.: 780 · 2.75 m.: 860 · 3.00 m.: 940 · 3.50 m.: 1100 · 4.00 m.: 1260**
Weight (kg)	**2.00 m.: 1020 · 2.25 m.: 1150 · 2.50 m.: 1280 · 2.75 m.: 1420 · 3.00 m.: 1540 · 3.50 m.: 1800 · 4.00 m.: 2150**
Transport width (mm)	**2.00 m.: 1950 · 2.25 m.: 2210 · 2.50 m.: 2470 · 2.75 m.: 2730 · 3.00 m.: 2990 · 3.50 m.: 3510 · 4.00 m.: 4030**
Row spacing (mm)	**2.00 m.: 130 · 2.25 m.: 130 · 2.50 m.: 130 · 2.75 m.: 130 · 3.00 m.: 130 · 3.50 m.: 130 · 4.00 m.: 130**
Recommended working speed (km/h)	**2.00 m.: 5 - 7 · 2.25 m.: 5 - 7 · 2.50 m.: 5 - 7 · 2.75 m.: 5 - 7 · 3.00 m.: 5 - 7 · 3.50 m.: 5 - 7 · 4.00 m.: 5 - 7**
Required power (hp)	**2.00 m.: 70 · 2.25 m.: 80 · 2.50 m.: 85 · 2.75 m.: 90 · 3.00 m.: 100 · 3.50 m.: 120 · 4.00 m.: 150**

БЕЛЕЖКИ

The YUKAY BARLAS universal seed drill is a mounted machine, attached to the tractor via a three-point hitch and driven by a wheel.
The continuously variable transmission ensures a uniform seed rate for each sowing tine, whilst the row spacing and sowing depth are adjustable. The independent press wheels reduce germination time by increasing seed-to-soil contact. The discs are symmetrically arranged and allow for planting at a row spacing of 13 cm, whilst the additional rake system works any seeds remaining on the surface into the soil. The seed drill is available with or without a fertiliser unit, with a row count ranging from 15 to 31, and can be fitted with a decametre and an electronic tracking system.

СНИМКИ

Докоснете снимка, за да я отворите в пълен размер.











